

STARCHEM

AntiFoam 1

Metalworking Fluid Additive

GENERAL DESCRIPTION

AntiFoam 1 is a very effective antifoam designed to control or eliminate excessive foaming in metalworking fluids and cleaners. **AntiFoam 1** can be used with soluble oil, semisynthetic, or synthetic metalworking fluids, and with all types of machine and part cleaners. The chemically modified silicones used in **AntiFoam 1** will not interfere with subsequent painting or plating operations.

APPLICATION

AntiFoam 1 is recommended at 1:5,000 (2 to 3 ounces for each 100 gallons of mix). Leaner dilutions up to 1:20,000 can be used in less severe applications.

Pour **AntiFoam 1** directly into the clean side of central systems, individual sumps or return troughs to maximize performance. **Note: Shake well before using.**

PHYSICAL PROPERTIES

Form	White, opaque liquid	Specific Gravity (H₂O=1)	1.01
Flash Point (COC)	Not Applicable	Density, lbs./gals.	8.4
Solubility in Water	< 0.1%		

AVAILABILITY

AntiFoam 1 is available in 1-quart containers, 1-gallon jugs, and 5-gallon pails.

HEALTH & SAFETY

The most recent MSDS is available from either **STARCHEM** or your authorized **STARCHEM** Distributor.

NOTES

- For Industrial Use only. Consult **STARCHEM** before using this product on any metals or applications not specifically recommended.
- Do not use any metalworking fluid additives except as recommended by **STARCHEM**.
- The general description, recommended uses, application data and statements in the product literature are guidelines. Because this product may be used for a variety of applications over which the manufacturer has no control, the manufacturer assumes no liability for incidental, consequential, or direct damages of any kind, regardless of causes, including negligence.

CIMCOOL® FLUID TECHNOLOGY

3000 Disney Street

Cincinnati, OH 45209

Tel (513) 458-8199 Fax (513) 458-8179